



NOTES:

1. STORM SEWERS AND SANITARY SEWERS TO BE LOCATED BETWEEN CURBS.
2. TELEPHONE, CABLE TV, AND HYDRO TO BE LOCATED ON ONE SIDE OF THE ROAD.
3. ANY PROPOSED PEDESTALS ON EXISTING ROADS SHALL BE PLACED IN THE SAME LINE AS EXISTING PEDESTALS.
4. ALL NEW & REPLACEMENT WOODEN UTILITY POLES IN A RURAL SECTION ARE TO BE TREATED, TO A MINIMUM OF 1.0m ABOVE THE EXISTING CENTRELINE ROAD GRADE.
5. SIDEWALKS MAY BE LOCATED ON EITHER, BOTH OR NEITHER SIDE OF ROADWAY.
6. SIDEWALKS TO BE 1.5m WIDE AND OFFSET 1.0m FROM PROPERTY LINE.
7. PAVEMENT WIDTH IS FACE OF CURB TO FACE OF CURB.
8. ALL OFFSETS ARE FROM PROPERTY LINE.

ROAD TYPE	R.O.W. WIDTH	GAS	HYDRO BELL CABLE T.V.	STREET LIGHT	BELL/ROGERS PEDESTALS IN NEW SUBDIVISIONS	HYDRANT	WATERMAIN	FROM P/L TO EDGE OF HYDRO FOUNDATION
MINOR COLLECTOR	23m	2.0m	2.75m	4.0m	4.0m	3.4m	5.0m	2.9m
MAJOR COLLECTOR	26m	2.0m	2.75m	4.0m	4.0m	3.4m	5.0m	2.9m
ARTERIAL MINOR	30m	3.0m	3.75m	5.0m	5.0m	3.4m	6.0m	2.9m
ARTERIAL MAJOR	34.5m	3.0m	3.75m	5.0m	5.0m	3.4m	6.0m	2.9m

ALL DIMENSIONS IN MILLIMETRES EXCEPT WHERE NOTED

THE CORPORATION OF THE TOWN OF WHITBY

PUBLIC WORKS DEPARTMENT

CHECKED	<i>[Signature]</i>
APPROVED	<i>[Signature]</i>
SCALE:	N.T.S

UTILITY LOCATIONS

DWG. DATE:	JUNE 1999
REVISION No.:	5
REVISION DATE:	JULY 2011
DWG No.	400